


103327-2 Product Details



103327-2

TE Internal Number: 103327-2



Active

 [View 3D PDF](#)

.100 inch AMPMODU Headers

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

Product Highlights:

- Connector
- Connector Type = Header - Pin
- Header Type = Breakaway
- 2 Positions
- Mating Post Length = 5.84 mm

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [ASSEMBLY, HEADER, BREAKAWAY, MOD II, SINGLE ROW, .10...](#) (PDF, English)

Catalog Pages/Data Sheets:

- [PERSONAL SYSTEMS PRODUCTS](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version S)
- [3D Model](#) (IGES, Version S)
- [3D Model](#) (STEP, Version S)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Connector Type = Header - Pin
- [Number of Positions](#) = 2
- [Mount Angle](#) = Vertical
- [PCB Retention Feature](#) = No
- [Surface Mount Compatible](#) = No
- [Board Standoff](#) = Without
- [Mounting Ears](#) = Without
- [Mating Connector Lock](#) = Without
- Post Size (mm [in]) = 0.64 [.025]
- Comment = Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths are available, consult Tyco Electronics.

Mechanical Attachment:

- Mating Post Length (mm [in]) = 5.84 [0.230]
- [Panel Attachment](#) = Without

Contact Related Features:

- [Contact Plating, Mating Area, Material](#) = Tin-Lead
- Contact Shape = Square
- Contact Base Material = Phosphor Bronze
- Approved Standards = UL E28476, CSA LR7189

Housing Related Features:

- Housing Material = Thermoplastic - GF
- Housing Flammability Rating = UL 94V-0

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C

Conditions for Usage:

- [High Temperature Housing](#) = No
- Operating Temperature (°C) = -65 - +105

Electrical Characteristics:

- Current Rating (Amps.) = 3
- Insulation Resistance (MΩ) = 5,000
- Dielectric Withstanding Voltage (V) = 750

Termination Related Features:

- [Termination Post Length \(mm \[in\]\)](#) = 3.05 [0.120]
- Solder Tail Contact Plating = Tin-Lead over Nickel

Body Related Features:

- [Header Type](#) = Breakaway
- Centerline (mm [in]) = 2.54 [0.100]
- Row-to-Row Spacing (mm [in]) = 2.54 [0.100]
- [Number of Rows](#) = 1
- [Selectively Loaded](#) = No
- [Mount Type](#) = Printed Circuit Board

Operation/ Application:

- [High Speed Serial Data Connector](#) = No

Other:

- Brand = AMP