

CATALOG

Cross Reference

[Competitive Products](#)[Military Spec P/Ns](#)[Tyco Brand P/Ns](#)[Part Number Search](#)[Document Search](#)[Product Type Search](#)[Product Family Search](#)[Alphabetical Search](#)[RoHS/ELV Compliance & Alternates](#)[CAD Model Search](#)[Brand Search](#)[Tool Search](#)[Multiple Part Comparison](#)[Lead Free Solutions](#)[Help/Glossary](#)[Home](#)

e-bulletin newsletter

SUBSCRIBE NOW!
click here

Subminiature and Microminiature D Connectors

↳ Stacked Connectors

AMP 750820-1  [Active](#)[Not ELV or RoHS Compliant](#)

(Corporate P/N: 750820-1)

[Search for Compliant \(RoHS/ELV\) Alternates](#)[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
General Info Sales Info Assembly Subcontractors	Pricing & Availability	Tooling

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240°C, Wave solder capable to 265°C
Connector Configuration [Upper Conn./Lower Conn.]:	Same Series
Gender:	Receptacle over Receptacle
Mating Connector Lock Type:	Threaded Insert, 4-40 UNC
Mating Polarization:	No
PCB Retention Feature:	With
Stacked Number of Positions [Upper Conn./Lower Conn.]:	26/26
Shell Type:	Full Metal Shell
Contact Mating Area Plating:	Gold (30)

Other Properties:

Pin/Socket:	Socket (Upper)/Socket (Lower)
PCB Mount Angle:	Right Angle
PCB Retention Method Feature:	Boardlocks
PCB Thickness (mm [in]):	2.36 [0.093]
Stacked Product Series [Upper Conn./Lower/ Conn.]:	.50 Series / .50 Series
Termination Post Length (mm [in]):	3.30 [0.130]
Rear Contact Shield:	With
Contact Material:	Phosphor Bronze
Solder Tail Plating:	Tin-Lead over Nickel
Housing Material:	Thermoplastic
Housing Material Flammability Rating:	UL 94V-0
Shell Material:	Steel
Shell Plating:	Tin over Copper
Contact Shield Material:	Phosphor Bronze

Centerline, Matrix (mm [in]):	1.27 x 2.54 [.050 x .100]
Product Series:	Slimline
Color Code:	None

Contact Shield Plating:	Tin
Bracket Material:	Zinc
Bracket Plating:	Tin-lead over Copper
Boardlock Material:	Copper Alloy
Boardlock Plating:	Tin-lead

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

