


INTERNATIONAL RECTIFIER **IR**

**AVALANCHE AND dv/dt RATED
HEXFET® TRANSISTORS**

- IRFR020**
- IRFR022**
- IRFU020**
- IRFU022**



N-CHANNEL

50 Volt, 0.10 Ohm HEXFET

The HEXFET® technology is the key to International Rectifier's advanced line of power MOSFET transistors. Efficient geometry and unique processing of the HEXFET design achieve a very low on-state resistance combined with high transconductance and great device ruggedness. HEXFETs feature all of the established advantages of MOSFETs such as voltage control, very fast switching, ease of paralleling, and temperature stability of the electrical parameters.

Surface mount packages enhance circuit performance by reducing stray inductances and capacitance. The D-Pak (TO-252AA) surface mount package brings the advantages of HEXFETs to high volume applications where PC Board surface mounting is desirable. The surface mount option IRFR020 is provided on 16mm tape. The straight lead option IRFU020 of the device is called the I-Pak (TO-251AA).

They are well suited for applications where limited heat dissipation is required such as, computers and peripherals, telecommunications equipment, DC/DC converters, and a wide range of consumer products.


Product Summary

Part Number	BV _{DSS}	R _{DS(on)}	I _D
IRFR020	50V	0.10Ω	15A
IRFR022	50V	0.12Ω	14A
IRFU020	50V	0.10Ω	15A
IRFU022	50V	0.12Ω	14A



FEATURES:


- Surface Mountable (Order As IRFR020)
- Straight Lead Option (Order As IRFU020)
- Fast Switching
- Low Drive Current
- Easily Paralleled
- Excellent Temperature Stability



Absolute Maximum Ratings


Parameter	IRFR020, IRFU020	IRFR022, IRFU022	Units
$I_D @ T_C = 25^\circ\text{C}$ Continuous Drain Current	15	14	A
$I_D @ T_C = 100^\circ\text{C}$ Continuous Drain Current	9.6	8.7	A
I_{DM} Pulsed Drain Current (1)	60	56	A
$P_D @ T_C = 25^\circ\text{C}$ Max. Power Dissipation	42		W
Linear Derating Factor	0.33		W/K (5)
V_{GS} Gate-to-Source Voltage	± 20		V
I_L Avalanche Current (2)	2.2 (See Fig. 14)		A
dv/dt Peak Diode recovery dv/dt (3)	2.0 (See Fig. 17)		V/ns
T_J Operating Junction Temperature Range	-55 to 150		$^\circ\text{C}$
T_{STG} Storage Temperature Range			$^\circ\text{C}$
Lead Temperature	300 (0.063 in. (1.6mm) from case for 10s)		$^\circ\text{C}$

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (Unless Otherwise Specified)

Parameter	Type	Mln.	Typ.	Max.	Units	Test Conditions
BV_{DSS} Drain-to-Source Breakdown Voltage	ALL	50	—	—	V	$V_{GS} = 0V, I_D = 250\mu\text{A}$
$R_{DS(on)}$ Static Drain-to-Source On-State Resistance (4)	IRFR020 IRFU020	—	0.080	0.10	Ω	$V_{GS} = 10V, I_D = 8.7A$
	IRFR022 IRFU022	—	0.10	0.12		
$I_{D(on)}$ On-State Drain Current (4)	IRFR020 IRFU020	15	—	—	A	$V_{DS} > I_{D(on)} \times R_{DS(on)}$ Max. $V_{GS} = 10V$
	IRFR022 IRFU022	14	—	—		
$V_{GS(th)}$ Gate Threshold Voltage	ALL	2.0	—	4.0	V	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$
g_{fs} Forward Transconductance (4)	ALL	3.6	5.4	—	S(O)	$V_{DS} \geq 50V, I_{DS} = 8.7A$
I_{DSS} Zero Gate Voltage Drain Current	ALL	—	—	250	μA	$V_{DS} = \text{Max. Rating}, V_{GS} = 0V$ $V_{DS} = 0.8 \times \text{Max. Rating}$ $V_{GS} = 0V, T_J = 125^\circ\text{C}$
		—	—	1000		
I_{GSS} Gate-to-Source Leakage Forward	ALL	—	—	500	nA	$V_{GS} = 20V$
I_{GSS} Gate-to-Source Leakage Reverse	ALL	—	—	-500	nA	$V_{GS} = -20V$
Q_g Total Gate Charge	ALL	—	25	38	nC	$V_{GS} = 10V, I_D = 15A$ $V_{DS} = 0.8 \times \text{Max. Rating}$
Q_{gs} Gate-to-Source Charge	ALL	—	5.0	7.5	nC	See Fig. 16 (Independent of operating temperature)
Q_{gd} Gate-to-Drain ("Miller") Charge	ALL	—	12	18	nC	(Independent of operating temperature)
$t_{d(on)}$ Turn-On Delay Time	ALL	—	8.7	13	ns	$V_{DD} = 25V, I_D = 15A, R_G = 18\Omega$
t_r Rise Time	ALL	—	55	83	ns	$R_D = 1.6\Omega$
$t_{d(off)}$ Turn-Off Delay Time	ALL	—	16	24	ns	See Fig. 15
t_f Fall Time	ALL	—	26	39	ns	(Independent of operating temperature)
L_D Internal Drain Inductance	ALL	—	4.5	—	nH	Measured from the drain lead, 6mm (0.25 in.) from package to center of die. Modified MOSFET symbol showing the internal inductances.
L_S Internal Source Inductance	ALL	—	7.5	—	nH	Measured from the source lead, 6mm (0.25 in.) from package to source bonding pad. 
C_{iss} Input Capacitance	ALL	—	400	—	pF	$V_{GS} = 0V, V_{DS} = 25V$
C_{oss} Output Capacitance	ALL	—	260	—	pF	$f = 1.0 \text{ MHz}$
C_{rss} Reverse Transfer Capacitance	ALL	—	44	—	pF	See Fig. 10

INTERNATIONAL RECTIFIER

Source-Drain Diode Ratings and Characteristics

Parameter	Type	Min.	Typ.	Max.	Units	Test Conditions
I_S Continuous Source Current (Body Diode)	ALL	—	—	15	A	Modified MOSFET symbol showing the Integral Reverse p-n junction rectifier. 
I_{SM} Pulsed Source Current (Body Diode) ①	ALL	—	—	60	A	
V_{SD} Diode Forward Voltage ④	ALL	—	—	1.4	V	$T_J = 25^\circ\text{C}$, $I_S = 15\text{A}$, $V_{GS} = 0\text{V}$
t_{rr} Reverse Recovery Time	ALL	57	130	310	ns	$T_J = 25^\circ\text{C}$, $I_F = 15\text{A}$, $di/dt = 100\text{A}/\mu\text{s}$
Q_{RR} Reverse Recovery Charge	ALL	0.17	0.34	0.85	μC	
t_{on} Forward Turn-On Time	ALL	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by $L_S + L_D$.				

Thermal Resistance

R_{thJC} Junction-to-Case	ALL	—	—	3.0	K/W ⑤	
R_{thCS} Case-to-Sink	ALL	—	1.7	—	K/W ⑤	Typical solder mount ⑥
R_{thJA} Junction-to-Ambient	ALL	—	—	110	K/W ⑤	Typical socket mount

- ① Repetitive Rating; Pulse width limited by maximum junction temperature (see figure 5)
- ② @ $V_{DD} = 25\text{V}$, Starting $T_J = 25^\circ\text{C}$, $L = 100\mu\text{H}$, $R_G = 25\Omega$, single pulse.
- ③ $I_{SD} \leq 15\text{A}$, $di/dt \leq 80\text{A}/\mu\text{s}$, $V_{DD} \leq 40\text{V}$, $T_J \leq 150^\circ\text{C}$
Suggested $R_G = 18\Omega$
- ④ Pulse width $\leq 300\mu\text{s}$; Duty Cycle $\leq 2\%$
- ⑤ $K/W = ^\circ\text{C}/W$
 $W/K = W/^\circ\text{C}$
- ⑥ Mounting pad must cover heatsink surface area. See case style drawing on front page.

The information shown on the following graphs applies also to the IRFU devices.




Fig. 1 — Typical Output Characteristics




Fig. 2 — Typical Transfer Characteristics




Fig. 3 — Typical Saturation Characteristics




Fig. 4 — Maximum Safe Operating Area




Fig. 5 — Maximum Effective Transient Thermal Impedance, Junction-to-Case Vs. Pulse Duration




Fig. 6 — Typical Transconductance Vs. Drain Current




Fig. 7 — Typical Source-Drain Diode Forward Voltage




Fig. 8 — Breakdown Voltage Vs. Temperature




Fig. 9 — Normalized On-Resistance Vs. Temperature

IRFR020, IRFR022, IRFU020, IRFU022 Devices

T-35-25

INTERNATIONAL RECTIFIER




Fig. 10 — Typical Capacitance Vs. Drain-to-Source Voltage




Fig. 11 — Typical Gate Charge Vs. Gate-to-Source Voltage




Fig. 12 — Typical On-Resistance Vs. Drain Current




Fig. 13 — Maximum Drain Current Vs. Case Temperature




Fig. 14a — Unclamped Inductive Test Circuit




Fig. 14b — Unclamped Inductive Waveforms




Fig. 15a — Switching Time Test Circuit




Fig. 15b — Switching Time Waveforms




Fig. 16a — Basic Gate Charge Waveform




Fig. 16b — Gate Charge Test Circuit




Fig. 17 — Peak Diode Recovery dv/dt Test Circuit

ORDERING INFORMATION

PACKAGING

IRFR Series — Tape and reel
 when ordering, add TR after the part number
 and the quantity
 (order in multiples of 3,000 pieces).

Example: IRFR020TR — 15,000 pieces.

